

pre-commit

pre-commit stage .

pre-commit install .git/hooks/pre-commit .

commit-msg , .

```
pre-commit install --hook-type commit-msg
```

hook-type

가 [hook-type](#)

```
{pre-commit,pre-merge-commit,pre-push,prepare-commit-msg,commit-msg,post-checkout,post-commit,post-merge,post-rewrite}
```

[pre-commit](#) ¹⁾ .

pre-commit

```
#!/usr/bin/env bash
# File generated by pre-commit: https://pre-commit.com
# ID: 138fd403232d2ddd5efb44317e38bf03

# start templated
INSTALL_PYTHON=/opt/homebrew/opt/python@3.9/bin/python3.9
ARGS=(hook-impl --config=.pre-commit-config.yaml --hook-type=pre-commit)
# end templated

HERE="$(cd "$(dirname "$0")" && pwd)"
ARGS+=(--hook-dir "$HERE" -- "$@")

if [ -x "$INSTALL_PYTHON" ]; then
    exec "$INSTALL_PYTHON" -mpre_commit "${ARGS[@]}"
elif command -v pre-commit > /dev/null; then
    exec pre-commit "${ARGS[@]}"
else
    echo '`pre-commit` not found. Did you forget to activate your
virtualenv?' 1>&2
    exit 1
fi
```

commit-msg

```
#!/usr/bin/env bash
# File generated by pre-commit: https://pre-commit.com
# ID: 138fd403232d2ddd5efb44317e38bf03

# start templated
INSTALL_PYTHON=/opt/homebrew/opt/python@3.9/bin/python3.9
ARGS=(hook-impl --config=.pre-commit-config.yaml --hook-type=commit-msg)
# end templated

HERE="$(cd "$(dirname "$0")" && pwd)"
ARGS+=(--hook-dir "$HERE" -- "$@")

if [ -x "$INSTALL_PYTHON" ]; then
    exec "$INSTALL_PYTHON" -mpre_commit "${ARGS[@]}"
elif command -v pre-commit > /dev/null; then
    exec pre-commit "${ARGS[@]}"
else
    echo '`pre-commit` not found. Did you forget to activate your
virtualenv?' 1>&2
    exit 1
fi
```

github auto reference

[Actions](#) [Projects](#) [Wiki](#) [Security](#) [Insights](#) [Settings](#)

Autolink references / Add new

Reference prefix *

This prefix appended by a number will generate a link any time it is found in an issue, pull request, or commit.

Target URL *

The URL must contain <num> for the reference number.

Preview: NEW-123 → <https://NEW.atlassian.net/browse/NEW-123>

[Add autolink reference](#)

.pre-commit-config.yaml

```
# See https://pre-commit.com for more information
# See https://pre-commit.com/hooks.html for more hooks

default_stages: [commit]
repos:
-   repo: https://github.com/pre-commit/pre-commit-hooks
    rev: v4.0.1
    hooks:
    -   id: trailing-whitespace
    -   id: end-of-file-fixer
    -   id: check-yaml
    -   id: check-added-large-files
-   repo: local
    hooks:
    -   id: jira-ticket-number-commit-msg
        name: Appending jira ticket number to commit message
        entry: bash -c 'bb --classpath hook --main prepare_commit_msg'
        stages: [commit-msg]
        language: system
    -   id: clj-kondo
```

```
name: Checking files with clj-kondo
entry: hook/clj-kondo.sh
stages: [push]
language: script
```

Plugin Backlinks:

1)

From:

<https://moro.kr/> - **Various Ways**

Permanent link:

<https://moro.kr/open/pre-commit>

Last update: **2022/05/19 07:28**

